Revision: 11.07.2024

Tel.: +49 (0)7156/357-0

# Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 7 (replaces version 6)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Product name PrimaSeal Plus
- · Article number: 11033-600000-000
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Priming
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

LOBA GmbH & Co. KG

Leonberger Straße 56 - 62

D-71254 Ditzingen

United Kingdom:

Phi House

Southampton Science Park

Southampton, SO167NS

United Kingdom

Phone +442380766722

- · Informing department: service@loba.de
- · 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

*P280 Wear protective gloves / eye protection.* 

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

(Contd. on page 2)

Printing date 11.07.2024 Version number 7 (replaces version 6) Revision: 11.07.2024

#### Product name PrimaSeal Plus

(Contd. of page 1)

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of the substances listed below with harmless additions.

· Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-xxxx	ethanol ♠ Flam. Liq. 2, H225; ♠ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	50-100%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol	≥10-<20%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate Flam. Liq. 3, H226;  STOT SE 3, H336, EUH066	8.5-10%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43-xxxx	butanone  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≤1%

· Additional information For the wording of the listed hazard phrases refer to section 16.

# **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact

In general, the product is not irritating to the skin. Wash off the product with plenty of soap and water after skin contact.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed Symptom Treat omatically.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

GF

Printing date 11.07.2024

Version number 7 (replaces version 6)

Product name PrimaSeal Plus

(Contd. of page 2)

Revision: 11.07.2024

# SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Prevent material from reaching sewage system, holes and cellars.

Inform respective authorities in case product reaches water or sewage system.

Dilute with much water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

# SECTION 7: Handling and storage

## · 7.1 Precautions for safe handling

Keep containers tightly sealed.

Store in cool, dry conditions in well sealed containers.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and containers: Store in cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

- · Storage class 3
- · 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

· 8.1 C	ontrol parameters				
Components with critical values that require monitoring at the workplace:					
64-17	-5 ethanol				
WEL	Long-term value: 1920 mg/m³, 1000 ppm				
67-63	-0 propan-2-ol				
WEL	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm				
123-8	6-4 n-butyl acetate				
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm				
<i>78-93</i>	-3 butanone				
WEL	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV				

(Contd. on page 4)

*Version number 7 (replaces version 6)* Printing date 11.07.2024

Product name PrimaSeal Plus

(Contd. of page 3)

Revision: 11.07.2024

### · Ingredients with biological limit values:

#### 78-93-3 butanone

BMGV 70 umol/L Medium: urine

> Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures Wash hands during breaks and at the end of the work.
- Breathing equipment:

Use breathing protection in case of insufficient ventilation.

Filter A/P2.

### · Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material:  $\geq 0.4$  mm

#### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

*Value for the permeation: Level*  $\leq 6$ 

· Eye/face protection Tightly sealed safety glasses.

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Colourless · Smell: Solvent-like Not determined. · Odour threshold: Not determined · Melting point/freezing point:

· Boiling point or initial boiling point and boiling

>78 °C range Highly flammable. · Flammability

2 Vol % · Lower: 19 Vol % · Upper:

10 °C (DIN EN ISO 3679) · Flash point:

370 °C · Auto-ignition temperature: Not determined. · Decomposition temperature:  $\cdot pH$ Not determined.

· Viscosity:

62-68 s (ISO 3 mm) · Kinematic viscosity at 20 °C · dynamic: Not determined.

(Contd. on page 5)

Printing date 11.07.2024 Version number 7 (replaces version 6) Revision: 11.07.2024

#### Product name PrimaSeal Plus

(Contd. of page 4)

Solubility
 Water: Fully miscible
 Partition coefficient n-octanol/water (log value)
 Steam pressure: Not determined.
 Not determined.

· Density and/or relative density

• **Density at 20 °C** 0.821 g/cm³ (Dichtekugel 10ml 20°C)

Relative densityVapour densityNot determined.Not determined.

· Particle characteristics not applicable, as liquid

· 9.2 Other information

· Appearance:

· Form: Fluid
· Important information on protection of health and

environment, and on safety.

· Self-inflammability: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/steam mixtures is possible.

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard classes
· Explosives Void
· Flammable gases Void
· Aerosols Void
· Oxidising gases Void

• Gases under pressure Void

· Flammable liquids Highly flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Void
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which emit flammable gases in contact with water
Void

Substances and mixtures, which emit flammable gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals Void
Desensitised explosives Void

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

# SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Revision: 11.07.2024

# Safety data sheet according to UK REACH

Printing date 11.07.2024

Version number 7 (replaces version 6)

#### Product name PrimaSeal Plus

			(Contd. of page 5
LD/LC50	values that	are relevant for classification:	\ 1°
64-17-5 et	hanol		
Oral	LD50	7,060 mg/kg (rat)	
Inhalative	LC50/4 h	20,000 mg/l (rat)	
67-63-0 pr	opan-2-ol		
Oral	LD50	5,840 mg/kg (rat)	
Dermal	LD50	13,400 mg/kg (rab)	
Inhalative	LC50/4 h	30 mg/l (rat)	
123-86-4 n	ı-butyl ace	tate	
Oral	LD50	14,000 mg/kg (rat)	
Inhalative	LC50/4 h	>21 mg/l (rat)	
78-93-3 bu	itanone		
Oral	LD50	3,300 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	12,000 mg/l (rat)	
		irritation Causes serious eye irritation.	
		other hazards	
· Endocrine		g properties	
78-93-3 b	utanone		List II

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

# SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

GB

Printing date 11.07.2024 Version number 7 (replaces version 6) Revision: 11.07.2024

Product name PrimaSeal Plus

(Contd. of page 6)

SECTION 14: Transport informat	
14.1 UN number or ID number ADR, IMDG, IATA	UNI 263
14.2 UN proper shipping name ADR	1263 PAINT (vapour pressure at 50°C not more the
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Kemler Number:	33 E E C E
EMS Number: Stowage Category	F-E, <u>S-E</u> B
14.7 Maritime transport in bulk according	g to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L Code: F2
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 50 ml  Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT (VAPOUR PRESSURE AT 50°C NO MORE THAN 110 KPA), 3, II

# SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

(Contd. on page 8)

Printing date 11.07.2024

Version number 7 (replaces version 6)

#### Product name PrimaSeal Plus

(Contd. of page 7)

Revision: 11.07.2024

## · Reportable explosives precursors

None of the ingredients is listed.

### · Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (\*).

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

## · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

## · Department issuing data specification sheet: Product safety

## · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

GB