

#### 2K ImpactOil Color

# Natural oil for highest standards and individual design

Colored 2K High Solid Oil for parquet and wood floors on natural basis. Gives the wood a gentle tone, highlighting the wood structure and the natural grain. Suitable for public and private areas with highest requirements, even for use in wet areas.

- 100 % natural solids completely solvent-free
- Excellent resistance to water and chemicals
- All colors can be mixed with one another
- · Low consumption, very economical
- Safe, simple and time-saving application in a 1-day system
- · Already usable after 24 hours
- Recommended for children's toys according to DIN EN 71-3
- Anti-slip certified according to BGR 181 and DIN 51130, evaluation group R10

#### Range of use

For coloring and preserving parquet and wood floors. For public and private areas with high traffic as well as areas exposed to high humidity, e.g. bathrooms, wellness areas etc. Suitable for almost all European and exotic wood species according to the LOBA suitability list, see LOBA product catalog and at www.loba.de.





#### PreTone

## Intensification of colors

Waterborne pigment stain for parquet and wood floors for color intensification in combination with natural oils. Highlighting the wood structure and grain results in very vibrant color effects.

- For significantly stronger colors
- Reduces oil-specific yellowing
- $\bullet \ \text{Safe and simple application} \\$
- Solvent-free and non-smelling
- Endless number of color combinations possible

### Range of use

On raw, carefully sanded wooden floors. Combining the watering process and pigmentation, intensive color effects are achieved. Together with the color range of the 2K ImpactOil Color there are endless design possibilities.



**Art.-no.** 10612

**Available** in 5 colors (2,5 l and 100 ml sample cans)


GISCODE W2+

## ImpactOil Color application – Optional with PreTone

- Please note our sanding recommendations for coloration
- Optional pre-treatment with PreTone to intensify the colors
- Apply the first layer of ImpactOil Color with Trowel, wait for it to penetrate
- Approximately 20 minutes after beginning the first layer, equalize with single disc machine and SpecialPad beige
- Apply the second layer of ImpactOil Color with Trowel, wait for it to penetrate
- Approximately 20 minutes after beginning the second layer, equalize with single disc machine and SpecialPad beige
- Walkable after 12 hours
- Consumption per layer: approx. 30 g/m<sup>2</sup>



2K ImpactOil Application videos









2K ImpactOil

